

EZ M Ø5"

INPUT VOLTAGE

120-277 V

OUTPUT

Up to 50 W ~ 90 lm/W

FINISH



CCT



MOUNTING OPTIONS

Wall Mount

ACCESSORIES AVAILABLE

Hex Louver, Glowing Ring,

Snoot (Available with

Different Finishes)

SQUARE Ø5"

INPUT VOLTAGE

120-277 V


OUTPUT

42 W ~ 82 lm/W

FINISH



CCT



MOUNTING OPTIONS

Surface Mount

Wall Mount

Stem Mount

*Standard or Slanted

ELEGANZA Ø5"

INPUT VOLTAGE

120-277 V


OUTPUT

20 | 28 W ~ 80-85 lm/W

FINISH



CCT



MOUNTING OPTIONS

Surface Mount

Pendant Mount

Wall Mount

Stem Mount

*Standard or Slanted

MAX Ø5"

INPUT VOLTAGE

120-277 V

OUTPUT

Up to 47 W ~ 73 lm/W

FINISH



CCT



MOUNTING OPTIONS

Surface Mount

Pendant Mount

Stem Mount

*Standard or Slanted

ACCESSORIES AVAILABLE

Hex Louver, Glowing Ring,

Pin Hole, Snoot (Available

with Different Finishes)

SLIM Ø3"

INPUT VOLTAGE

120-277 V


OUTPUT

15 W ~ 80 - 85 lm/W

FINISH



CCT



MOUNTING OPTIONS

Surface Mount

Pendant Mount

Stem Mount

*Standard or Slanted

SLIM HO Ø3"

INPUT VOLTAGE

120-277 V

OUTPUT

30 W ~ 85 - 95 lm/W


HEIGHT

10", 16", 25"

FINISH



CCT



MOUNTING OPTIONS

Surface Mount

Pendant Mount

Stem Mount

*Standard or Slanted

90 CRI

LUMEN
TUNABLE

ELEGANZA SERIES