

# THALASSA ET6150

## OUTDOOR PRODUCTS

Square Sconce

The Thalassa outdoor surface mounted square LED fixture was created with a sleek design deliberately, so it could blend in with many different outdoor building styles. The Thalassa also has an impressive efficacy of 95 LPW providing performance as well as elegance in the install environment. Finally, this product is a complete aluminum die cast offering an unparalleled sense of finesse, fixture strength and quality.



eralux®



DATE

PROJECT NAME

TYPE

QTY

ORDERING CODE

ET6150-C40

-

-

-80

-

-DMG

### OPERATING & ELECTRICAL

INPUT VOLTAGE 100-277Vac

POWER FACTOR 0.9

DIMMING 0-10V external dimming down to 10% (with SDMG option)

TOTAL HARMONIC DISTORTION (THD) <20%

### PERFORMANCE

LUMENS PER WATT ~95 LPW at 80CRI

POWER CONSUMPTION 40W

BEAM ANGLE 15°, 24°, 36°, 50°

### WARRANTY

#### SYSTEM WARRANTY – 5 YEARS

Eralux will warrant defective drivers, LEDs and boards for 5 years from the date of purchase. This warranty is valid only if the fixture is installed and used as per installation guides and specifications. If a defect is present, Eralux will send drivers and boards at no fee with a thorough replacement instructions along with instructions on the return of the defective parts back to Eralux.

LUMEN MAINTENANCE – L85 at 50,000 hours

Rated for 85% initial lumen output at 50,000 hours of operation, operated at 25°C ambient temperature; per guidelines published by the Illuminating Engineering Society (IES). (L85 at 50,000 hours)

### APPLICATION CONDITION

AMBIENT TEMPERATURE RANGE -25 to 50°C

PROTECTION IP65

### COMPATIBLE MOUNTING

MOUNTING Wall mount

### MECHANICAL & HOUSING

HOUSING Aluminum die cast

LENS Highly durable, shatterproof tempered glass lens ensures high efficiency light output for a clean, evenly illuminated surface with minimal glare.

FINISH ERALUX white, black, gray, bronze, silver (RAL9006) powder coat finish

POWER SUPPLY Factory wired electronic LED driver

LED BOARD COB

# THALASSA ET6150

OUTDOOR PRODUCTS

Square Sconce

|               |                           |
|---------------|---------------------------|
| DATE          |                           |
| PROJECT NAME  |                           |
| TYPE          |                           |
| QTY           |                           |
| ORDERING CODE | ET6150-C40 - - -80 - -DMG |

## ORDERING GUIDE

EXAMPLE: ET6150-C40-3-8-80-W-DMG

| FIXTURE FAMILY                                                                                 | POWER                                   | CCT                    | BEAM ANGLE                   | CRI                  | FINISH                                                 | CONTROLS                                                   |
|------------------------------------------------------------------------------------------------|-----------------------------------------|------------------------|------------------------------|----------------------|--------------------------------------------------------|------------------------------------------------------------|
| <b>ET6150</b>                                                                                  | <b>-C40</b>                             | <b>-</b>               | <b>-</b>                     | <b>-80</b>           | <b>-</b>                                               | <b>-DMG</b>                                                |
| <b>ET6150</b><br>ERALUX Thalassa<br>ET6150 outdoor<br>wall mounted<br>square sconce<br>fixture | <b>-C40</b><br>40 watts:<br>3658 lumens | <b>-3</b><br>3000K CCT | <b>-15</b><br>15° beam angle | <b>-80</b><br>80 CRI | <b>-B</b><br>Black powder<br>coat finish               | <b>-DMG</b><br>0-10V<br>external<br>dimming<br>down to 10% |
|                                                                                                |                                         |                        | <b>-24</b><br>24° beam angle |                      | <b>-W</b><br>White powder<br>coat finish               |                                                            |
|                                                                                                |                                         | <b>-4</b><br>4000K CCT | <b>-36</b><br>36° beam angle |                      | <b>-S</b><br>Silver (RAL9006)<br>powder coat<br>finish |                                                            |
|                                                                                                |                                         |                        | <b>-50</b><br>50° beam angle |                      | <b>-G</b><br>Gray (RAL7012)<br>powder coat<br>finish   |                                                            |
|                                                                                                |                                         | <b>-5</b><br>5000K CCT |                              |                      | <b>-Z</b><br>Mineral bronze<br>powder coat<br>finish   |                                                            |

# THALASSA ET6150


OUTDOOR PRODUCTS

Square Sconce

|               |            |   |   |     |   |      |
|---------------|------------|---|---|-----|---|------|
| DATE          |            |   |   |     |   |      |
| PROJECT NAME  |            |   |   |     |   |      |
| TYPE          |            |   |   |     |   |      |
| QTY           |            |   |   |     |   |      |
| ORDERING CODE | ET6150-C40 | - | - | -80 | - | -DMG |

## DIMENSIONS

EXAMPLE: ET6150-C40-3-8-80-W-DMG



# THALASSA ET6150

OUTDOOR PRODUCTS

Square Sconce

|               |                           |
|---------------|---------------------------|
| DATE          |                           |
| PROJECT NAME  |                           |
| TYPE          |                           |
| QTY           |                           |
| ORDERING CODE | ET6150-C40 - - -80 - -DMG |

## LUMEN ESTIMATE

Lumen output varies based on CCT and CRI. An estimate of lumen output of the various CCT/CRI combinations, use correction factors as per table below:



| LUMEN ESTIMATE ADJUSTMENT FACTORS |       |       |       |       |
|-----------------------------------|-------|-------|-------|-------|
| CCT                               | 2700K | 3000K | 3500K | 4000K |
| NORMAL (80CRI)                    | 0.94  | 1     | 1.02  | 1.03  |

## PHOTOMETRIC DATA



GRID DISTANCES WITH A MOUNTING HEIGHT OF 10' AFG

POLAR LUMINOUS INTENSITY GRAPHS

ET6150-C40-3-18-80



ET6150-C40-3-62-80



# THALASSA ET6150

OUTDOOR PRODUCTS

Square Sconce

|               |                           |
|---------------|---------------------------|
| DATE          |                           |
| PROJECT NAME  |                           |
| TYPE          |                           |
| QTY           |                           |
| ORDERING CODE | ET6150-C40 - - -80 - -DMG |

## ACCESSORIES

Ordered separately, field installed

## EMERGENCY LED DRIVER (BLD-CM20N-480800-8W)

BLD-CM20N-480800-8W



OUTPUT POWER : 8 WATTS



- Easy Wiring
- Certified For CA Title 20
- Constant Power Performance

BLD-CM20N-480800-8W LED Emergency Driver is UL listed for field and factory installation that allows the same LED fixture to be used for both normal and emergency operation. In the event of a power failure, the emergency driver switches to emergency mode and operates the fixture for 90 minutes. The unit contains a battery, charge, and converter circuit in a single enclosure. This module will operate a LED array load at 8W with constant power at a rated output voltage of 25-48 VDC. The constant power design of BLD-CM20N-480800-8W maintains the output wattage to the LED array, providing consistent illumination for the entire emergency runtime. Its slim shape is ideal for use indoor or outdoor LED lighting fixtures, such as linear lights, wall packs or sconces, etc.

## DIMENSIONS (inches and mm)



# THALASSA ET6150

OUTDOOR PRODUCTS

Square Sconce

|               |                           |
|---------------|---------------------------|
| DATE          |                           |
| PROJECT NAME  |                           |
| TYPE          |                           |
| QTY           |                           |
| ORDERING CODE | ET6150-C40 - - -80 - -DMG |

## OVERVIEW

### PREMIUM MATERIALS

Constructed from aluminum die-cast enhancing thermal heat dissipation while providing excellent figure strength.

### LIGHT SOURCE

Downlight outdoor sconce.



### MULTIPLE BEAM ANGLES

Customize your fixture with a unique set of beam angles in the up light or downlight orientation with the option to having a 20-degree tilt towards the wall.

### MULTIPLE FINISH OPTIONS

Select from black, white, or silver powder coat anti-cracking finishes to accent your project space.

### CRI

80 CRI provides greater rendering allowing for a more natural light look.